

Bosch Video Management System v.4

www.boschsecurity.com



BOSCH
Invented for life



The Bosch Video Management System is a unique enterprise IP video security solution that provides seamless management of digital video, audio, and data across any IP network. It is designed to work with Bosch CCTV products as part of a total video security management system. You can integrate your existing components into one easy-to-manage system, or use our full-line capabilities and benefit from a complete security solution based on cutting-edge technology and years of experience.

The Bosch Video Management System allows a very flexible system design:

- Compact: Single Site System
1 to 2000 cameras out of the box.
Only this system supports BIS-BVMS connectivity.
- Enterprise: Multi Site-Single Customer
Up to 10,000 cameras
Supporting multi-site requirements for Metro, Airport and other large industrial facilities
Consisting of individually configured servers
Combined monitoring in Operator Client
- Enterprise: Multi Site-Multi Customer
Up to 10,000 cameras
Up to 10 individually configured subsystems
Enabled for legally different companies

The Bosch Video Management System is installed on a Microsoft Windows Operating System.

- ▶ Enterprise-class Client/Server based video management system
- ▶ Superior alarm handling with alarm priorities and selectable user group distribution
- ▶ Mobile video client for live and playback
- ▶ Edge based intelligent Video Analytics (IVA) and forensic search
- ▶ Support of 3rd party cameras that are compliant to ONVIF Profile S

We recommend using Bosch Workstations and Servers. They are fully tested and optimized for Bosch Video Management System.

In addition to the Bosch ST standard terms and conditions of sale, the Bosch Video Management System Software is a great option to benefit from the Bosch maintenance service, keeping your VMS always up-to date.

It can be found in your online CCTV product catalog.

System overview

The Bosch Video Management System contains the following software components:

- Management Server software provides management, monitoring, and control of the entire system
- Enterprise Management Server provides access to multiple Management Server computers
- Video Recording Manager (VRM) provides recording and playback management of video, audio, and data
- Configuration Client software provides the user interface for system configuration and management
- Operator Client software provides the user interface for system monitoring and operation
- Mobile Video Service, Mobile Client
- Video Streaming Gateway

These software components can be run together on a single PC for small systems or on separate PCs and servers for large systems.

Bosch Video Recording Manager (VRM) provides a Distributed Network Video Recorder solution, eliminating the need for dedicated NVRs. The VRM provides load balancing and failover for the iSCSI storage and makes it easy to add additional iSCSI storage later on. VRM introduces the concept of a storage virtualization layer. This abstraction layer enables VRM to manage all of the individual disk arrays in the entire system as a single “virtual” common pool of storage, which is intelligently allocated as needed. The usage of multiple client workstations offers great scalability.

The Bosch VMS manages 2000 IP cameras / encoders per Management Server (up to 10,000 in Enterprise Systems). A Bosch VMS supports 100 workstations.

Functions

Deployment

- Updates of Operator Client and Configuration Client automatically deployed from Management Server
- Supports all Bosch MPEG4 & H.264 encoders, MPEG4 & H.264 IP cameras and IP AutoDome cameras in SD & HD format, decoders, Allegiant, DiBos, Bosch POS/ATM Bridge, and DiBos-compatible ATM Bridge
- Supported HD resolutions: 720p and 1080p

Configuration

- Enterprise System: Operator Client can access up to 10 Management Servers simultaneously
- Support of 3rd party cameras that are compliant to ONVIF Profile S
- Intelligent Video Analysis (IVA) and Forensic Search without servers
- Connectivity to mobile clients (iPad and iPhone, App available in AppStore)
- Automatic scan of IP devices
- Automatic IP address assignment of IP devices
- Batch firmware updates of IP devices
- Configurable Logical Tree
- Pre-configured camera sequences with 25 cameras with each up to 100 steps with individual dwell times.
- “Automatic Sequences” created by multiple selection and drag and drop to Image panes
- 4 configurable user-events (can be triggered via menu command)

User Interface

- Zoomable sitemaps with links, devices, sequences, and Command Scripts
- Automatic map positioning of a camera in a map when this camera is selected
- Sitemaps in DWF format are used. DWF format version 5.0 and 6.0 are supported.
- Up to 4 PC monitors supported per Workstation
- CCTV keyboard support, connected to either Workstation or IP decoder
- CCTV keyboard support the Enterprise System (select the desired Management Server)
- Flexible Image panes allow any combination of video window sizes and layouts
- Any live Image pane can be switched to instant playback

- Multiple instant playback Image panes
- Image windows can display live video, instant playback video, text documents, maps, or web pages
- Device states shown by icons, including network-connection loss, video loss, and camera de-adjustment
- Favorites tree can be individually configured per user
- Favorites tree can include complete views with Image pane layouts and camera assignments
- Bookmarks in Live and Playback Mode for easy investigation and export of recordings
Selected clips can be exported to DVD, network drives, or USB sticks with a few mouse clicks
- Camera selection by double-click or drag and drop from site maps, Logical Tree, or Favorites Tree
- Decoders can be organized in Monitor Walls from within Operator Client
- Monitor Walls can be controlled without connection to Management Server
- Control of analog monitors connected to decoders via drag and drop
- Sophisticated multi-camera timeline allows easy, graphical searching of stored video
- Timeline colors indicate recording status – normal recording, alarm recording, motion recording, protected recording, and audio recording (not for cameras managed by a VRM)
- Easy clip selection by dragging hairlines in the timeline
- Flexible search works across all DVRs connected to the system
- Post-recording motion search allows easy locating of changes in selected areas
- Forensic Search allows the usage of Intelligent Video Analysis (IVA) algorithms on the recorded video
- Two audio listening options – selected channel only, or multiple simultaneous channels
- Audio Intercom functionality
- 4:3 and 16:9 Image panes
- Continuous Operation for live, playback and export while Management Server disconnected
- Live and Playback of the following recording engines: Video Recording Manager, Local Storage, Direct-iSCSI-Recording, Bosch Recording Station, Video Streaming Gateway. For legacy purposes the following recording engines are supported: NVR, DiBos, Vidos NVR

Scheduling

- Up to 10 Recording schedules with Holidays and Exception Days
- Task Schedules with Holidays, Exception Days, and recurring schedule support
- Per camera settings for minimum and maximum recording times
- Per camera, per recording schedule frame rate and quality settings for live, normal recording, motion recording, and alarm recording

Event Handling

- Compound events (combining events with Boolean logic)
- Event duplication allowing separate handling
- Event allocation to user groups

- Schedule dependent event logging
- Schedule dependent event-generated Command Script invocation

Alarm Handling

- Schedule dependent alarm generation
- Alarms can trigger alarm-mode recording for any cameras
- 100 alarm priorities
- Selective auto-popup on alarm
- Alarms displayed in separate alarm window
- Up to 5 Image panes per alarm with live or playback video, sitemaps, documents, or web pages displayed in an “alarm row”, with highest priority alarms on top
- Audio file per alarm
- Workflow with user instructions and user comments, optionally forced before clearing
- Email or SMS notification on alarm
- Alarm display on Monitor Wall
- Alarm auto clear options either time or state dependent

User Management

- LDAP compatible for integration with user management systems such as Microsoft Active Directory
- Access to system resources individually controlled per user group
- Logical Tree customized per user group – users only see devices for which they have access
- User group rights for protecting, deleting, exporting, and printing video
- User group rights for Logbook access
- User group priority assignment for PTZ control and Allegiant camera access
- Individual per-camera privileges assignable per user group for live access, playback, audio, meta data display, dome control
- Dual-authorization logon – special privileges and priorities granted when two users log on together

System Monitoring

- System-wide health monitoring, including Bosch cameras, computers, software, and network equipment
- Network equipment and other third-party devices monitored with SNMP

Customization and Interfacing

- CameoSDK for easy integration into 3rd party Physical Security Information Management (PSIM) and other Management Systems
- RemoteClient Enterprise SDK for system integrators wanting to interface a running Bosch VMS Operator Client.
- Custom Command Scripts can control all system functionality
- Built in Command Script editor supporting C# and Visual Basic .Net
- External software can trigger events and send metadata via “Virtual Inputs”
- Any .Net programming language (C#, JScript, etc.) or COM programming language (C++, Visual Basic, etc.) can be used to interface Bosch VMS functionalities

- Other systems can control a virtual matrix with Allegiant CCL commands that can be sent via RS232
- Compatible with Bosch Building Integration System
- Compatible with Advantech ADAM-6000 series Digital Input / Output modules

Parts included

- The Base Box is delivered with DVD and Quick Start Manual.
- The DVD contains the following items:
 - Installation program that can selectively install all components (Management Server software, Video Recording Manager software, Configuration Client software, Operator Client software, Video Streaming Gateway software, Mobile Video Services software) in all supported languages
 - Configuration Manual (PDF format) in all supported languages (except Arabic)
 - Operator’s Manual (PDF format) in all supported languages (except Arabic)
- Quick Start Manual in English, French, German, Simplified Chinese and Spanish

Licenses are provided as eLicenses via email.

Technical specifications

System Specifications

Maximum number of workstations simultaneously viewing the same camera	Multicast: 50 Unicast: 5
Supported languages	English, German, Dutch, Italian, Portuguese, French, Spanish, Simplified Chinese, Traditional Chinese, Russian, Hungarian, Japanese, Czech, Danish, Finnish, Greek, Norwegian, Polish, Swedish, Thai, Turkish, Korean, and Arabic

Anti-Virus software must not perform a full-scan. Performance may decrease depending on configuration.

Event reaction time	<1 second, assuming sufficient network bandwidth
Alarm reaction time (incl. 1 live Image pane, 1 instant playback Image pane and 1 map Image pane):	Maximum 2 seconds, assuming sufficient network bandwidth
Bandwidth requirements	Min. 1 Gbps for connections between: Operator Client to Management Server Operator Client to VRM/DiBos Management Server to NVR/VRM/DiBos

Required open ports

Connection to Video Streaming Gateway

TCP port 8756

Connection to (Enterprise) Management Server:

TCP ports 5390, 5392, 5393, 5395, 5396

Connection to Operator Client Workstations by BVMS SDK:
TCP port (default 5394)

Connection from Management Server to SMTP (for email notifications):
TCP port 25

Connection to Bosch encoders and decoders:
Control channel: TCP ports 80 and 1756
Network scan: UDP ports 1757 and 1758
Multicast detection: one selectable UDP port (default 1800)
Multicast video transmission:
For each encoder audio or video stream, 1 selectable UDP port
Unicast UDP transmission: UDP ports dynamically assigned in the range from 1024 to 65000

Connection between Management Server and DiBos (as of V.8.10., earlier versions need a patch for using Web service):
TCP port 808

Connection between Operator Client and DiBos DVRs (uses DCOM):
TCP Port 135 plus four TCP ports and four UDP ports dynamically assigned in the range from 1025 to 65535
These ports are also used when Management Server and an old DiBOS 8.9 or earlier without patch are connected.

Management Server Specifications

Maximum number of sustained events	For highest performance server: 500 events/s with Logbook 1000 events/s without Logbook 5000 events/s at peaks with Logbook
Logbook	Supported by SQL Server 2008 R2 (64-bit version) 4 GByte Logbook size
Management Server Redundancy	Available with VMware HA. Please contact Bosch Design Engineer for redundancy solutions.
Maximum number of Task Schedules	200

VRM Specifications

Maximum count of VRM servers per Management Server	40
Maximum data rate per iSCSI	Please contact Bosch Design Engineer for iSCSI storage solutions.
Max. number of playback sessions	64

Minimum Client Workstation PC Requirements

Operation System	Windows 7 Professional or Ultimate SP1 64 bit version (required for > 500 cameras)
CPU	Intel Core 2 Duo
RAM	2 GB or greater 4 GB or greater for Enterprise Operator Clients
Free disk space	3 GB or more for Single Site Systems

	5 GB or more for Enterprise Systems We recommend having minimum 15% free disk space.
Network card	1000Base-T
Display Resolution	Minimum per monitor 1024x768, 1280x1024 or greater recommended
Recommended Graphic Card	MHW-AWGC-Q4000 MHW-AWGC-Q5000

Maximum Graphic Cards Specifications

You find detailed information on the maximum number of Image panes and the CPU load for various workstations or servers and graphic cards in the Application Guide “Display performance indication”.

Minimum Management Server PC Requirements

Operation System	Windows 2008 Server R2 SP1 (64-bit) required for > 500 cameras Window 2003 Server R2 SP2 (32-bit only) for NVR only For All-in-one systems and maximum 64 IP cameras/ encoders: Windows 7 Professional or Ultimate SP1 (64-bit only)
CPU	Intel Core 2 Duo Intel Core 2 Quad for systems > 500 cameras
RAM	4 GB or greater 8 GB for systems > 500 cameras
Free disk space	15 GB or greater We recommend having minimum 15% free disk space.
Network card	1000Base-T
Display Resolution	1024x768 or greater

Minimum VRM Server PC Requirements

Operation System	Windows 7 Ultimate SP1, Professional Edition SP1 64-bit versions Windows Server 2003 R2, Standard Edition, 64-bit versions Windows Server 2008 R2, Standard Edition 64-bit versions Windows Storage Server 2008, Standard Edition 64-bit versions
CPU	Dual-Core Intel Xeon Processor 5110 (1.60 GHz, 1066 FSB) to Quad-Core Intel Xeon Processor E5430 (2.66 GHz, 1,333 FSB)
RAM	Minimum 2 GB
Free disk space	500 MB We recommend having minimum 15% free disk space.

Network card	1000Base-T
Display Resolution	1024x768 or greater

Mobile Client Requirements

Link to App Store	www.boschsecurity.com/ MobileVideoService
Maximum number of Mobile Video Service instances per Management Server	5
Number of simultaneous connections per Mobile Video Service (1 mobile device consumes 1 connection, each stream consumes another connection)	20
Server for Mobile Video Service	Windows Server 2008/R2 or Windows 7 SP1 Professional or Ultimate 64-bit versions
Supported cameras	IP cameras with H.264 support that are directly controlled by Bosch VMS (not controlled by BRS or VIDOS)
iOS Version for iPhone/iPad	5.1.1

Minimum NVR Server PC Requirements

Operation System	Windows XP Professional, SP3 (32-bit only), Windows 2003 Server, R2 SP2 (32-bit only) Windows 7 and Windows Server 2008 not supported
CPU	Intel Core 2 Duo
RAM	2 GB or greater
Free disk space	500 MB + Video Storage We recommend having minimum 15% free disk space.
Hard disk drives	Minimum: separate partition for video storage Separate drive for video storage recommended
Network card	1000Base-T
Display Resolution	1024x768 or greater

Device Compatibility

Barco Monitor Wall	Barco RCPPlusAgent.exe 2.0.6.12 for Barco Monitor Wall
Analog Matrix Switch	Bosch Allegiant series, firmware 8.75 or later and Master Control Software version 2.92
CCTV Keyboard	Bosch Intuikey (KBD-Universal or KBD-Digital), firmware version 1.96

Digital I/O	Digital I/O Advantech ADAM-6050, ADAM-6052, ADAM-6060, ADAM-6066
Digital Video Recorder	Bosch Recording Station 8.10 DiBos, firmware version 8.7 Maximum 100 DiBos/BRS recorders per Management Server
USB to Serial adapter	Belkin serial adapter cable F5U103vea
Ethernet to Serial adapter	Control DeviceMaster RTS 4-Port
IP Devices	VIP-X Series encoders and cameras H.264 Series encoders and cameras MPEG-4, H.264 Main Profile, H.264 Baseline Plus are supported (H.264 Baseline and MPEG-2 not supported)
Connectivity with Building Integration System	Version 2.5 TU1

Ordering information

Demoversion - Non Expandable

Order number **MBV-BDEM-40**

Lite-32-Edition - Non Expandable

Order number **MBV-BLIT32-40**

Lite-64-Edition - Non Expandable

Order number **MBV-BLIT64-40**

Professional Edition

Order number **MBV-BPRO-40**

Enterprise System

2 Workstations, 2 subsystems, 1 CCTV Keyboard
Supports 1 Enterprise Management Server, 2 subsystems (Management Servers)
Order number **MBV-BENT-40**

Enterprise Subsystem Expansion

Supports 1 Management Server as member of an Enterprise System
Order number **MBV-XSUB-40**

Enterprise Upgrade for Pro

Supports 1 Management Server to be upgraded to an Enterprise Management Server
Order number **MBV-FEUP-40**

1 Channel Expansion

Order number **MBV-XCHAN-40**

1 Workstation Expansion

Order number **MBV-XWST-40**

1 DVR Expansion

Order number **MBV-XDVR-40**

1 CCTV Keyboard Expansion

Order number **MBV-XKBD-40**

1 Forensic Search Expansion

Order number **MBV-XFOREN-40**

Allegiant Matrix Connection

Order number **MBV-FALG-40**

ATM/POS Connection

Order number **MBV-FATM-40**

OPC Server Connection for BIS

Order number **MBV-FOPC-40**

Mobile Video Service Expansion

Supports 1 ???

Order number **MBV-XMVS-40**

Base Box

Hard cardboard box including DVD and Quick Start Manual (in English, French, German, Simplified Chinese, and Spanish)

Order number **MBV-BBOX**

Services

Maintenance Demoverion

Order number **MBV-MDEM**

Maintenance Lite-32-Edition

Order number **MBV-MLIT32**

Maintenance Lite-64-Edition

Order number **MBV-MLIT64**

Maintenance Professional Edition

Order number **MBV-MPRO**

Maintenance Enterprise Edition

Order number **MBV-MENT**

Maintenance Enterprise Subsystem Expansion

Order number **MBV-MSUB**

Maintenance Mobile Video Service

Order number **MBV-MMVS**

Maintenance Enterprise Upgrade for Pro

Order number **MBV-MEUP**

Maintenance Channel Expansion

Order number **MBV-MCHAN**

Maintenance Workstation Expansion

Order number **MBV-MWST**

Maintenance DVR Expansion

Order number **MBV-MDVR**

Maintenance CCTV Keyboard Expansion

Order number **MBV-MKBD**

Maintenance Forensic Search Expansion

Order number **MBV-MFOREN**

Maintenance Allegiant Matrix Connection

Order number **MBV-MALG**

Maintenance ATM/POS Connection

Order number **MBV-MATM**

Maintenance OPC Server Connection

Order number **MBV-MOPC**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com